

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Texture Remover
PRODUCT CODE: 0374

HMIS CODES: H F R P
1 1 0

-----SECTION I - MANUFACTURER IDENTIFICATION-----

MANUFACTURER'S NAME: Litex, Inc.
ADDRESS: 5985 NW 31 Avenue, Fort Lauderdale, FL 33309
EMERGENCY PHONE: 954-970-0361 **INFORMATION PHONE:** 800-340-0361
DATE PREPARED: 10-30-2003 **NAME OF PREPARER:** Eugene O'Neill

---SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION---

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS				VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
		OSHA PEL	ACGIH TLF	OTHER			
None							

-----SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS-----

BOILING POINT: 201°F **SPECIFIC GRAVITY (H₂O=1):** 1.1
VAPOR DENSITY: Lighter than Air **EVAPORATION RATE:** Slower than Ether
COATING V.O.C.: 2.53 LB/GL (303 GR/LT)
SOLUBILITY IN WATER: Product is miscible with water
APPEARANCE & ODOR: Clear and odorless

-----SECTION IV - FIRE & EXPLOSION HAZARD DATA-----

FLASH POINT: 199°F **METHOD USED:** CC
FLAMMABLE LIMITS IN AIR BY VOLUME: LOWER: 1.3% **UPPER:** 9.5%

EXTINGUISHING MEDIA: n/a

SPECIAL FIREFIGHTING PROCEDURES: Firefighters should be equipped with self-contained breathing apparatus and turn-out gear. Do not enter fire space without full bunker gear.

UNUSUAL FIRE & EXPLOSION HAZARDS: There are no known unusual or explosion hazards.

-----**SECTION V - REACTIVITY DATA**-----

STABILITY: Stable

CONDITIONS TO AVOID: Avoid open flames, welding arcs and other high temperature sources that may produce thermal decomposition.

INCOMPATIBILITY (MATERIALS TO AVOID): Reducing agents and high alkaline medium.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: None known

HAZARDOUS POLYMERIZATION: Will not occur

-----**SECTION VI - HEALTH HAZARD DATA**-----

INHALATION HEALTH RISKS & SYMPTOMS OF EXPOSURE: Excessive inhalation of vapor or mist can cause headache, nausea, irritation of nose, throat and lungs.

SKIN & EYE CONTACT HEALTH RISKS & SYMPTOMS OF EXPOSURE: May cause severe eye irritation and possible corneal damage. Prolonged or repeated skin contact may produce irritation.

SKIN ABSORPTION HEALTH RISKS & SYMPTOMS OF EXPOSURE: Apparent symptoms would be redness and burning.

INGESTION HEALTH RISKS & SYMPTOMS OF EXPOSURE: Swallowing of the product may cause some gastrointestinal irritation.

HEALTH HAZARDS (ACUTE & CHRONIC): Repeated and prolonged occupational overexposure may produce nasal and respiratory irritation. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

CARCINOGENICITY: NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known

EMERGENCY & FIRST AID PROCEDURES:

For eye contact: Flush with lukewarm water for 15 minutes. Seek medical advice if necessary.
For skin contact: Flush with lukewarm water. Remove contaminated clothing and launder before re-use.
For inhalation: Remove exposed individual to fresh air. Contact a physician if necessary.
For ingestion: Rinse out mouth immediately. Give exposed individual 6-8 ounces of liquid. Do not induce vomiting unless advised by a physician.

-----**SECTION VII - PRECAUTIONS FOR SAFE HANDLING & USE**-----

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

- For small spills: Use absorbent material such as vermiculite or any other floor absorbent.
For large spills: Eliminate all ignition sources or persons not wearing protective equipment from the area.

WASTE DISPOSAL METHOD: Do not flush water to sewer, watershed or waterway. Use absorbent or kitty litter to dry product before disposal. Dispose of product with applicable local, county, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE: Keep material from freezing. Do not store above 120°F or below 34°F. Close container after each use. Keep out of reach of children. Use adequate ventilation when handling or applying this product.

OTHER PRECAUTIONS: None

-----**SECTION VIII - CONTROL MEASURES**-----

RESPIRATORY PROTECTION: None specified.

VENTILATION: Adequate ventilation required if used in confined area.

PROTECTION GLOVES: Wear protective gloves that are impermeable such as neoprene or resistant gloves such as butyl rubber.

EYE PROTECTION: Chemical splash goggles would be ideal but safety glasses in compliance with OSHA recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: To reduce or prevent skin contact, wear impervious clothing or boots.

WORK/HYGIENIC PRACTICES: Wash hands thoroughly before eating or using restroom.

-----**SECTION IX - DISCLAIMER**-----

DISCLAIMER: The above information refers to the product as currently manufactured. A common practice is end-user incorporating additives to thin, reduce or provide different characteristics. When this is done, the chemical composition of the product and attendant hazards may be altered. Litex is not liable.